

パラフィール・ロープ仕様

ターミナル使用での 破断強度 (Kg)	外径 mm		芯糸の断面積 mm ²		空中での重量 Kg/100m		海水での重量 Kg/100m		最小巻き径 mm	
	タイプA	タイプF	タイプA	タイプF	タイプA	タイプF	タイプA	タイプF	タイプA	タイプF
225	4.5		3.98		1.5		0.03		10	
500	7		7.97		3.7		0.1		15	
1,000	8.5		15.94		5.6		0.4		30	
1,500		7		7.64		3.7		0.1		15
2,000	11		31.88		9.4		1		60	
3,000		8.5		15.28		5.4		0.3		30
3,500	13.5		55.8		14.2		1.7		80	
5,000	17		79.7		21.5		1.8		100	
6,000		11		30.56		9		0.6		70
7,500	20		119.6		30		2.7		150	
10,000	22		159.4		37.5		5		200	
10,000		13.5		53.47		14.4		1.7		90
15,000	27.5	17	239.1	76.3	58	22	7	1.8	300	120
20,000	31		318.8		74		10		350	
22,500		20		114.6		29.5		2		170
30,000	36	22	478.3	152.8	99	36.8	14	5	700	240
50,000	45		797.1		160		30			
60,000	49	31	956.5	305.6						
90,000		36		458.3						
100,000	63.5		1594		310		50			
150,000		45		763.9						
200,000	90		3188		560					